



Industrial Oils, Fluids & Lubricants

# Technical Data Sheet (TDS)

## Metalworking Concentrate 1060

### Product Description

Metalworking Concentrate 1060 is a honey colored high viscosity fluid with a multitude of uses in metalworking applications.

### Features and Benefits

Metalworking Concentrate 1060 can be used on both ferrous and non-ferrous metals. The high viscosity promotes excellent cooling properties by dissipating the heat. The anti-weld, extreme pressure agent promotes outstanding performance with tool life and finishes.

### Applications

Metalworking Concentrate 1060 is recommended for severe metalworking applications of both ferrous and non-ferrous. Machining applications may include cutting, drilling, milling, tapping, threading, broaching, tube bending, grinding, and sawing operations. May be used as an additive to metalworking oils to improve performance, tool life, and finishes on parts.

Consult your account manager or our technical support team for questions regarding compatibility.

### Typical Properties

#### Property

API Base Oil Category  
Appearance  
Density lb/gal.  
Specific Gravity  
Viscosity @ 40 C (cSt)  
Pour Point, F  
Flash Point (COC) F  
Chlorine, wt %  
Sulfur, wt %  
Lubricity wt. %

#### Specifications

Paraffins  
Thick honey colored  
10.0  
1.20  
>460  
< 30  
None  
100  
0  
0

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, variations that do not affect performance are to be expected during normal manufacturing. The Safety Data Sheet (SDS) must be consulted for appropriate information regarding the safe handling, storage, and disposal of a product.

Far West Oil Company, Inc.  
139 West Mindanao Street, Bloomington, Ca. 92316  
Phone: (909) 873-1500 Fax: (909) 873-1501  
website: [www.farwestoil.com](http://www.farwestoil.com)  
email: [sales@farwestoil.com](mailto:sales@farwestoil.com)