



Industrial Oils, Fluids & Lubricants

Technical Data Sheet (TDS)

Gear Oil GL-1 ISO 220

Product Description

Gear Oil GL-1 ISO 220 is a high quality machine gear box mineral oil. Product is formulated with anti-wear and extreme pressure agents for maximum performance.

Features and Benefits

The rust and oxidation inhibitors provide excellent metal protection along with extending the life of the product. The extreme pressure agents allow for the machine to carry high loads.

Applications

Use as is for lubrication of industrial machine gear boxes. Always check manufacturer's recommendation for proper viscosity grade.
Consult your account manager or our technical support team for questions regarding compatibility.

Typical Properties

<u>Property</u>	<u>Specifications</u>
Appearance	Amber
Density lb/gal.	7.708
Specific Gravity	0.925
Viscosity @ 40 C (cSt)	220
Pour Point, F	< 0
Flash Point (COC) F	>330
Chlorine, wt % Sulfur,	0
wt %	0
Lubricity wt. %	0

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, variations that do not affect performance are to be expected during normal manufacturing. The Safety Data Sheet (SDS) must be consulted for appropriate information regarding the safe handling, storage, and disposal of a product.

Far West Oil Company, Inc.
139 West Mindanao Street, Bloomington, Ca. 92316
Phone: (909) 873-1500 Fax: (909) 873-1501
website: www.farwestoil.com
email: sales@farwestoil.com