



Industrial Oils, Fluids & Lubricants

Technical Data Sheet (TDS)

Metalworking Oil 1281

Product Description

Metalworking Oil 1281 is a mineral oil based industrial networking fluid containing sulfur and lubricity additives.

Features and Benefits

Metalworking Oil 1281 can be used on both ferrous and non-ferrous metals, except brass and copper. The low viscosity promotes outstanding performance with chip removal, less residue on the parts for cleaning operations and reduced oil consumption.

Applications

Metalworking Oil 1281 is recommended for honing applications of both ferrous and non-ferrous metals. Do not use for brass and copper. Consult your account manager or our technical support team for questions regarding compatibility.

Typical Properties

<u>Property</u>	<u>Specifications</u>
API Base Oil Category	Napthenic
Appearance	Brown
Density lb/gal.	7.499
Specific Gravity	0.90
Viscosity @ 40 C (cSt)	19
Pour Point, F	< 0
Flash Point (COC) F	>300
Chlorine, wt %	0
Sulfur, wt %	4 - 5
Lubricity wt. %	9 - 10

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, variations that do not affect performance are to be expected during normal manufacturing. The Safety Data Sheet (SDS) must be consulted for appropriate information regarding the safe handling, storage, and disposal of a product.

Far West Oil Company, Inc.
139 West Mindanao Street, Bloomington, Ca. 92316
Phone: (909) 873-1500 Fax: (909) 873-1501
website: www.farwestoil.com
email: sales@farwestoil.com