



Industrial Oils, Fluids & Lubricants

# Technical Data Sheet (TDS)

## Waylube Oil #3

### Product Description

Waylube Oil #3 is a premium quality oil formulated with anti-wear, rust and oxidation inhibitors, and tacktifier additives.

### Features and Benefits

The rust and oxidation inhibitors provide excellent metal protection along with extending the life of the product. The extreme pressure agents allow for the machine to carry high loads. Tacktifier additives provide excellent adhesion properties allowing the oil to adhere to slideways longer for maximum protection.

### Applications

Use as is for lubrication of machine tool horizontal and vertical slideways. Always check manufacturer's recommendation for proper viscosity grade.

Consult your account manager or our technical support team for questions regarding compatibility.

### Typical Properties

<u>Property</u>	<u>Specifications</u>
API Base Oil Category	Napthenic
Appearance	Amber
Density lb/gal.	7.685
Specific Gravity	0.923
Viscosity @ 40 C (cSt)	150
Pour Point, F	< 0
Flash Point (COC) F	>330
Chlorine, wt %	0
Sulfur, wt %	0
Lubricity wt. %	0

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, variations that do not affect performance are to be expected during normal manufacturing. The Safety Data Sheet (SDS) must be consulted for appropriate information regarding the safe handling, storage, and disposal of a product.

Far West Oil Company, Inc.  
139 West Mindanao Street, Bloomington, Ca. 92316  
Phone: (909) 873-1500 Fax: (909) 873-1501  
website: [www.farwestoil.com](http://www.farwestoil.com)  
email: [sales@farwestoil.com](mailto:sales@farwestoil.com)